
2025/08/01 21:08 1/5 Features

DSEQ32 (aka yet another TR clone) is based on the classic TR drumsequencers

see trsequencer for more drumsequencer designs



Features

- 32 step 8 track drum seq, each step has trig/acc/roll
- one track can be used as note track for bass sequencing
- independant length/tempo divisor for each track, all can be synced to a master track
- 8 banks of 16 patterns
- patterns are saved on a bankstick
- song mode (not sure how I will implement this..)
- all functions can be executed while running
- forward/backward playing direction
- 24 PPO resolution
- midi clock master/slave (maybe also taptempo)
- settings are stored on internal eeprom

note that these features are not final!

Last update: 2006/11/19 23:23

Interface

- lcd: displaying (bpm pat trknr edited_par)
- 32 step buttons + stepleds, leds are dual color to display trig/acc
 - step edit behaviour: step off/trig/trig+acc
 - all functions are accessed with a stepkey + shift combination
 - pattern selection: stepkey + pattern button
 - track select/mute: stepkey + track button
- rotary encoder for bpm, also used for editing values
- Step button layout:
 - Track layer

1	2	3	4	5		6	7	8	9	10	11	12	13	14	15	16
Select	Selec	t Sele	ct Sel	ect S	elect	Select	Select	Select	Selec	Selec	tSelect	Select	Select	Selec	tSelect	Select
Trk1	Trk2	Trk3	Trk	:4 T	rk5	Trk6	Trk7	Trk8	Trk9	Trk10	Trk11	Trk12	Trk13	Trk14	Trk15	Trk16
17	18	19	20	21	22	23	24	25	26	27	28	29 3	30	31	32	
Mute	Mute	Mute	Mute	Mute	Mut	e Mute	Mute	Mute	Mute	Mute	Mute	Mute I	Mute	Mute	Mute	
Trk1	Trk2	Trk3	Trk4	Trk5	Trk6	Trk7	Trk8	Trk9	Trk10	Trk11	Trk12	Trk13	Γrk14	Trk15	Trk16	

Pattern layer

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
Select	Select	Select	Select	Select	Select	Select	Select	Select	Select	Select	Select	Select	Select	Select	Select
1.	Bank B	Bank C	Bank D	Bank E	Bank F	Bank G	Bank 8								
17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32
Select	Select	Select	Select	Select	Select	Select	Select	Select	Select	Select	Select	Select	Select	Select	Select
Pat 1	Pat 2	Pat 3	Pat 4	Pat 5	Pat 6	Pat 7	Pat 8	Pat 9	Pat 10	Pat 11		Pat 13		_	Pat 16

• Function layer

1	2	3	4	5	6		7		8		9			10	1	1	12		13	14	15	16
Cut	Сору	Paste	Delete	NoteNi	Ler	ngth	Div	/isor	No	rma	ΙΑ	ccer	nt (Cut	С	Сору	Pas	ste	Delete	Format	Midi	Fwd/Backwd
Track	Track	Track	Track	Track	Tra	ick	Tra	ick	Ve	locit	y V	eloc	ity	Patte	ern P	atteri	n Pat	ttern	Pattern	Bankstick	Mode	Playdir
17	18	1	_9	20	21/2	22 2	23	24	25	26	27	28	29	30	31	32	2					
Fill	Mid	iCh N	4idiCh												LCD	R	ese	t				
Tracl	k Dru	m N	loteSe	q											Mod	de Se	eq					

Progress

- first prototype
- new layout design
- ledmatrix/buttonmatrix finished (see matrix page)
- frontpanel finished/wired
- first take on controll surface handler (step, track and pattern handling)
- sequencer works, timing is not stable yet

2025/08/01 21:08 3/5 Features

- made a temporary case
- fixed flickering leds when pushing a button
- bankstick error handling added
- default pattern is loaded when no BS is available at startup
- independant length/divider for each track implemented
- LCD optimalisations
- loading and saving of patterns works now
- backward playing direction implemented
- midi mode implemented with simple slave mode (no interpolation)
- improved bpm handling (pattern bpm is saved with pattern)
- fill function implemented
- CS interface improved (the edit functions are now accessed with stepbutton+shift)
- settings are saved in internal eeprom
- notetrack implemented, this track will be used to program basslines
- changed data structure, new pattern is 256bytes
- cs is updated for notetrack (shift + track selects notetrack)
- shift + stop resets the song position
- due to code/ram space limitations the project is ported to a pic18f4620
- the core board was modified so that the backlight can be controlled by the software
- new bankstick routines to handle the larger pattern size
- 2 new functions added: Seq Reset and Backlight mode
- CC layer added

Software

most of the software will be written in C, some of the critical parts will be optimised in ASM to increase performance

the software will be based on the midibox clockbox example uCApps

- Data structure
- Application code
 - Bankstick code (updated)
 - Control surface code
 - Sequencer core code
 - Sequencer get/set and helper rountines
 - control surface code

Hardware

Components:

- CORE module CORE Module uCApps
- DOUTX3 DOUT Module uCApps
- DINX1 DIN Module uCApps
- BANKSTICK BANKSTICK Module uCApps

The leds/buttons are wired in a matrix configuration to reduce the number of DIN/DOUT modules needed DSEQ32 matrix

Development

First prototype:

forum topic



used for development of data structure, bankstick code, sequencer core

New version:

- Construction of frontpanel
- Wiring of the 32 step leds/buttons
- Testing of the step buttons with the SM_example application
- Testing of the step leds with modified SM_example app (modified version includes leddriver)
- Development of user interface code
- · Button and led handling finished
- The flickering led problem is solved with MIOS v 1.9c
- Encoder handling works, but there's still a small bug
- Updated LCD layout for new functions
- The leds to indicate play/save/vel/special function button work now
- Some LCD optimalisations
- Development of seq code
- Sequencer edit functions work as expected
- Sequencer runs!
- Fixed sequencer mute track bug
- Some tracks didn't send the note off messages correctly, corrected
- Bankstick error handling added
- Default pattern is loaded when no BS is available at startup
- Note length/divider is implemented

2025/08/01 21:08 5/5 Features

• Independant length/divider for each track

back to user_projects

From:

http://www.midibox.org/dokuwiki/ - MIDIbox

Permanent link:

http://www.midibox.org/dokuwiki/doku.php?id=dseq32&rev=1163978537

Last update: 2006/11/19 23:23

