I've tested PICPgm v0.9.9.3 with my JDM programmer and it works. This version has support for burning the "ID Locations", which is required for the bootloader and MIOS. It also supports PIC18F452, PIC18F4620, PIC16F88 and PIC18F4685.

1/1

and the second	Hardware Ab	out
🦻 🟩 🗰 🗰	) 🛍 💢	6
Common Code Memory EEPF	ROM Memory Co	onfig Word
Select HEX File		
the state of the s		100 m
F:\projects\work\pic\16f648ad	demo\demo.H 💌	Browse
F:\projects\work\pic\16f648ad	demo\demo.H 👱	Browse
F:\projects\work\pic\16f648ac	demo\demo.H _	* L
		* L
Locations Code Memory (FLASH)	Device Infor PIC: Device Id:	mation PIC16F648A 0x1100
Locations Code Memory (FLASH) Data Memory (EEPROM)	Device Infor PIC: Device Id: Flash:	mation PIC16F648A 0x1100 8 kByte
Locations Code Memory (FLASH)	Device Infor PIC: Device Id:	mation PIC16F648A 0x1100

Download here.

NOTE: The "ID Locations" are shown differently to ICProg. ICProg (and the MIDIbox doco) shows the ID locations as an 8 byte (16 hex digit) string, with the Device ID as the byte on the far right. In PICPgm, this is the last value in the list (location 20007)

From: http://www.midibox.org/dokuwiki/ - **MIDIbox** 

Permanent link: http://www.midibox.org/dokuwiki/doku.php?id=jdm\_with\_picpgm



Last update: 2007/01/22 00:45