


# EASY CV

Test Equipment: CV-Destination MB33 MAM:



## Introduction

All Parameters are saved as a preset as a song (programchange...)

Digital created LFO+ENV with CV-Output.

No Displays, No Menues, Minimal buttons, much Scopes, much Led-Ring-Rotarys (LRE-8x2CS)  
one big UI with complete functions for one LFO+ENV Voice + 4xChannelstrip Controlls...

LFO+ENV are mixed together softwareside, to use only one CV-Output

Each Channel = Filter need 8xCV-Outputs

Copy Paste for LFOs and ENvelopes between the Voices

Copy Paste for a Song aka Preset aka Bank aka Program(change)

Jam Style Pattern load (next Preset Display) + Preset Morph between Current-Preset and Next-Preset

The Early Design was a EuroRack-Module: A Breakoutmodule for each CV-Output, with Depth-rotary, Focusswitch (Pushrotary), 2x Scopes (LFO+ENV) and LFO/ENV-Switch to show on one Display the Mixed Waveform & to switch the Rotary to "ENV" or "LFO" Mode (there is only space for one Encoder - maybe just make PAN Style, instead of 2 individual level -maybe more live feel?, how ever when using an 3Stage switch, i could disable MIX-View, or display it on ENV or LFO...maybe a good choise ;) ) The Depth-rotary has no Ledring, want to display it as a bar or as Value in the scope...

# FrontPanel

## Brain

THE LEFT SIDE of the BRAIN > Preset-Management: **Save & Load** the PROGRAM, can be done by Midi-ProgramChange -or With the **LOAD-PRESET**-Encoder then press **LOAD** -or **Morph** to the next Program slowly with the MORPH-Encoder  
 -Another option is to take a **PUSH-ENCODER** for **LOAD & STORE** > and load and store it by pushing it... would free 2 buttons for other functions.

MORPH?:


-The Upper 7 Segment LED- Display: is the **LOAD Display** indicate the new Program with ENV+LFO -  
 The downer 7 Segment LED- Display: is the **STORE Display** it indicates also the current Program with ENV+LFO

-with morph you crossfade between both Presets (be carefull, first Store the current Preset

**Paste & Copy** do their job @ the whole PROGRAM Memory

**ENV-PASTE & ENV-COPY** do their job @ the selected Envelope > (ENV-Voice selection is done by the breakout Modules) ... LFO..same

Midi-Channel Note NR or Number of Envelope is a real programmer job (C), with usb-upload from computer .... this is a individual device, and once set, it has to play > and it just should do LFOs and Envelopes Fixed routed, no generic, special > in my case for a filterbank.



THE RIGHT SIDE of the BRAIN > LFO + ENV Settings (one Voice): ADSR with:

**CURVE** Parameter which give exponentially to it (no straight lines While Fall and Rise)

**Short:** just shorten the Maximal length of a Envelope, having more Feeling on Encoders should change Scope Display also...

**LFO:** get synced with Midi, and there is a retrigger by Notes...

**Phase:** offsets the start-Phase

**Delay:** simple delay (nte-Trig)

**Rate:** clear from 8 wholes to 128th or so

**Wave:** access to the Waveforms

**Duration:** interpret Midisync in trippled, whole notes or whatever...

**DEPTH:** is the maximal Value of FALL and RISE and SUSTAIN, i know i loose resolution with this...but i have to have a memory filterbank,...doing depth instead with Potentiometers on Filtermodules... would give no memory...

## BreakOut

**this will not be supportet > since i dont want a Euro-Module Setup > i want one big filterbox.**

1. Discharged UserInterface for the Brain in "Island mode" (Scopes + Digital-CV-Amount)
2. CV-Breakout EuroModule to be located near the CV-Destination (example: a Filter).

2 Waveforms (ENV+LFO) are mixed together softwareside

that bring 2 advanteges:

1. save one CV-Output
2. the Amplitude of each Waveform is saved in the patch, so the CV-Amount to a Filter is saved in the Patch

That bring 2 disadvantages:

1. LFO or ENV cant get patched to individual destination
2. the Resulation gets lower 2 very low, and the code has to be adptet much... or have to be made from scratch Because I use the device for a Memory-Filterbox (VCF+VCA), i am ok with the pros and cons, so i call it EASY-CV



**Envelope Scope:** show the ENV-Waveform  
or the Mixed-CV-Output-Waveform (when Switch is in LFO Mode)  
and show the Envelope-Amount with a BAR or as numeric Value?

**MIXED CV Plug:** CV-Output > Mixed Waveform ENV+LFO

**Switch @ ENV:**

1. Depth-Encoder change ENV Amount of the CV-MIX
2. ENV Scope will show ENV Wave
3. LFO Scope will Show CV-Mix

**Switch @ LFO:** visa versa ENV

Press the Encoders built in **ENCODER-BUTTON:**

will switch the BRAIN-A-D-S-R and L-F-O ENCODER to the Page for THIS Module...

workflow, see what you have with a Scope, over a filter, and edit exact this selected CV on the brain in full detail...

### VCA-VCF


#### CVs(AOUT):

- 1.VCF-CUT
- 2.VCF-RES
- 3.FILTER DRIVE
- 4.VCA-ENV
- 5.VCA-DRIVE
- 6.DRY-WET (Original vs Filtered Mixer)
- 7.Send 2 EFX1
- 8.Send 2 EFX2

So 1x 8AOUT-Module for each "Channelstrip", makes a total of 4x8AOUT-Modules. The Module of Choise is a 16Bit, since i control with the the same AOUT-Channel ENV+CUT-OFF... so there is no analog potentiometer for Cutoff or resonance... it is all saved in the Preset.

the VCA is basicly a simple VCA (MS20Like) or something  
the VCF are a 303 18dB for the 24db Filter it will be a SSM2044, where boards are available.


#### Original Schematics 303 - VCA-VCF



In order to not use those **overprized MATCHED-PAIR-TRANSISTORS** (over 2€ on the cheapest place) i have to use standart Transistors and make a **VBE-MATCH** on my own, i have already a PCB from here - to measure the transistors with a Multimeter: <https://midisizer.com/other/vbe-matching/>

#### Example for a Filterbank

Here are 8 Envelopes 4x for VCF 4x for VCA... in fact there could be used more than this for example 8x VCF and 8x VCA... since the BREAK-OUT-Modules are Modular, and they share the same "Main-UI"... the only limiting factor is the CODE... i am not a C-Guru, and maybe i will still have timing problems with 8x CV-Outs... we will see.



THE BRAIN - LEFT SIDE  
Preset-Management:  
Save and Load the "SONG" or call it "BANK"  
The Song is loaded by ProgramChange  
On.  
With the LOAD-PRESET-Encoder  
BUT it will not be heard  
you must first press-LOAD  
or Morph to it slowly with MORPH-Encoder  
MORPH!  
You have the NEW-ENV+LFO @ LOAD  
You have the current ENV+LFO @ ACTUAL  
with morph you crossfade between both

Paste, and Copy do their job @ the full BANK  
ENV-PASTE ENV-COPY do their job @ the selected Envelope  
(selection is done by the breakout-Modules)


Midi-Channel Note NR or Number of Envelope is  
a real-programmer job, with usb-upload from computer  
...

this is a individual device, and once set, it has to play  
and it just should do LFOs and Envelopes  
fixed routed, no generic, special

in my case for a filterbank.

MPE-CV/Brain & UI-MAIN (Scopes + Digital CV-Amount)  
ated near the CV-Destination (e.g. a Filter).  
together software-side

is saved in the patch, so the CV-Amount to a Filter is saved in the Patch!  
Individual destination  
w, and the code has to be adapted much... or have to be made from scratch  
ry-Filterbox (VCF+VCA), i am ok with the pros and cons, so i call it Simple-CV



- I will use it to filter:
- 2xGuitar-Loopstations
- 1xGuitar
- 1xPercussion-Master

A not EUROMODULE-BASED Version of something like this is the FILTERBOX: (this is the Design i prefer @ the moment)



## General Design

The Panel is made of transparent but shaded (black transparent) Plexiglass.

The Panel is directly mounted into a Flightcase.

The 3x LRE8x2 (LED RING) are mounted with the Encoder Nuts, the rest of the PCBs are mounted with normal thru-hole screws.

## FrontPanel

### PCBs

**The Analog-IO Board on the Backpanel, holds:**

- the ENV-VCAs
- the DryWet-VCAs, Filter-Relay-Switch
- SEND-EFX-VCAs
- the Summing Mixer
- the Ducking-Cross-AMP-Follower+Ducking-VCAs
- VCF+ENV-VCA-Distortion-Driver-VCAs

-the Connectors to connect the Filter, AOOUT, Poti-Boards


Left-Part of the Brain on Breathboard:

OLED-Display

Button: ShadowSE/ITT

ENCODER: with built in Pushswitch

a early state with 7Segment Displays to indicate the Patches



### 1. UI Parts Listing

#### BRAIN + BREAKOUT

- 6,3 Neutrik Connector
- [FLASH-Switch @ Rs-components](#)

Value	Type	Qty
Switch	SPDT Vertical PCB-Mount ON-OFF-ON	1

 **Fix Me!** Fill Table

#### Pots / Knobs

- [Alps RK11K Series](#)
- [Alpha Pots @ Thonk](#)
- [Knobs Suppliers](#)

-  **Fix Me!** which Values for the Audio-Mixer?

### 3.Footprint Making in KiCAD

- ALPS Pots
- Alpha Pots

- 6,3mm Jack
- Switch
- Momentary Switch
- SSD-Displays
- OLED Display
- Rotary Encoder

 **Fix Me!** have to be done

#### 4. Schematics in KiCAD

 **Fix Me!** have to be done

#### 5.PCB Making In Kicad

##### PCB Making Order

- BRAIN PCBs:
  - a.Left-Brain
  - b.Right-Brain
- 3x LRE8x2CS - is a generic PCB which i already have (fairlightiiís)
- Backpanel PCB
- FILTER PCBs

From:  
<https://www.midibox.org/dokuwiki/> - **MIDIbox**

Permanent link:  
[https://www.midibox.org/dokuwiki/doku.php?id=easy\\_cv&rev=1471135004](https://www.midibox.org/dokuwiki/doku.php?id=easy_cv&rev=1471135004)

Last update: **2016/08/14 00:36**

